


Conductivity Electrodes

innoSens 350

The innoSens range of conductivity electrodes offers durability, reliability and high performance for a wide range of conductivity monitoring applications, from ultrapure water to stock solution measurements.

Applicable Controllers

innoCon 6800C Intelligent Conductivity Controller、innoCon 6501C Basic Conductivity Controller、Flumsys 10TC Controller

<div>innoSens 350-0.01 Conductivity Electrodes</div>	<div>Order No.: 35-0350-01</div> <div></div>	<div>Measuring range0.01-200.0μS/cm</div> <div>Temperature probePT1000</div> <div>Working temp0-100°C(Optional high temperature electrode)</div> <div>Max. Pressure6bar</div> <div>InstallationPipe installation</div> <div>Connection methodChucks</div> <div>Cable length5m standard</div> <div>Two-stage electrode, 316L material, suitable for pure water, ultrapure water</div>
<div>innoSens 350-0.1 Conductivity Electrodes</div>	<div>Order No.: 35-0350-02</div> <div></div>	<div>Measuring range0.1-2000μS/cm</div> <div>Temperature probePT1000</div> <div>Working temp0-100°C(Optional high temperature electrode)</div> <div>Max. Pressure6bar</div> <div>InstallationPipe installation</div> <div>Connection methodChucks</div> <div>Cable length5m standard</div> <div>Two-stage electrode, 316L material, suitable for raw water, pure water</div>
<div>innoSens 350 Conductivity Electrodes</div>	<div>Order No.: 35-0350-03</div> <div></div>	<div>Measuring range0-200mS/cm</div> <div>Temperature probePT1000</div> <div>Working temp0-100°C(Optional high temperature electrode)</div> <div>Max. Pressure6bar</div> <div>InstallationPipe installation</div> <div>Connection methodChucks</div> <div>Cable length10m standard</div> <div>Quadrupole electrode, PP/316L material, suitable for medium water, raw liquid, etc.</div>

